



# // RAPID HIGH PRESSURE INFLATABLE TENTS

## APPLICATION FIELDS



Fire department, rescue service and aid organisation



Civil defence



Triage, field hospitals, first aid posts



Military



Weatherproof Shelter for Sensitive Equipment and Workshops



The RAPID tent has a fully integrated structure in which the side walls, roof, gable and floor form a single unit. The design and the anchoring system ensure high stability and wind resistance.

- **LOW TO NO MAINTENANCE REQUIRED**
- **WIDE RANGE OF ACCESSORIES AVAILABLE**
- **QUICK AND EASY ASSEMBLY AND DISASSEMBLY**
- **SELF-ERECTING STRUCTURE, VERSATILE, RELIABLE AND ROBUST**

# // RAPID HIGH PRESSURE INFLATABLE TENTS

The RAPID tent is a high pressure, medium weight shelter, inflated by compressor, that requests a simple logistic support to deploy. Designed for extreme weather conditions, RAPID tents can be connected to each other, length- and crosswise as well as to other shelters like containers or vehicles. The inflatable structure consists of high-pressure arches inflated at 8 bar, making the tent impervious to temperature fluctuations. Overpressure valves prevent overfilling.

The optimal solution when low weight, fast deployment combined with high comfort are important factors. The tent is fully integrated, meaning that sidewalls, roof, gables and floor are welded together, and the inflatable frame is mounted. The interior can be easily divided into sections by means of partition walls, creating separate rooms or cabins.

## ADVANTAGES

- Simple maintenance in field operations
- Not influenced by temperature changes
- Simple erection - no special tools required
- Integrated PVC - flooring protecting against surface water and reptile/bugs
- Flexible inflatable structure with high pressure arches
- The three-layer windows allow for natural light and ventilation

## SCOPE OF DELIVERY

- Main tent
- Connector
- Pegs
- Hammer
- Repair kit

White

Sand

Dark Green



	RAPID 504	RAPID 506	RAPID 508	RAPID 606	RAPID 608	RAPID 610
Base area	20.00 m <sup>2</sup>	30.00 m <sup>2</sup>	40.00 m <sup>2</sup>	36.00 m <sup>2</sup>	48.00 m <sup>2</sup>	60.00 m <sup>2</sup>
Length	4.00 m	6.00 m	8.00 m	6.00 m	8.00 m	10.00 m
Width	5.00 m	5.00 m	5.00 m	6.00 m	6.00 m	6.00 m
Ridge height	2.70 m	2.70 m	2.70 m	3.00 m	3.00 m	3.00 m
Packing size	160 x 80 x 95 cm	120 x 80 x 110 cm	160x80x100 cm	150x100x110 cm	200 x 80 x 80 cm	200 x 80 x 90 cm
Weight	158 kg	188 kg	204 kg	260 kg	336 kg	354 kg
Operating pressure	6-8 bar	6-8 bar	6-8 bar	6-8 bar	6-8 bar	6-8 bar
Windows	4	6	8	6	8	10
Guy ropes	10	12	14	12	14	16
Anchoring points	16	18	20	18	20	22

\* Other colors are available upon request.

## OPTIONS AND ACCESSORIES

Extra groundsheet  
 Partition walls  
 Inner liner  
 Sunroof  
 Side entrances  
 Connection modules  
 Entrance modules  
 Compressor  
 Rigid modular flooring  
 Lights  
 Power distributors/switchboards  
 HVAC  
 Lettering/branding

# LANCO

LANCO  
 Dr. Lange GmbH & Co. KG  
 Sure Wisch 6  
 30625 Hannover

Telephone: +49 (0)511 367155-0  
 Fax: +49 (0)511 367155-140  
 Email: info@lanco-tents.com  
 Internet: www.lanco-tents.com