



// DECONTAMINATION SHOWERS

APPLICATION FIELDS



Fire department, rescue service and aid organisation



Triage, field hospitals, first aid posts



Military



Industry and commerce



Decontamination plays an important part in hazard prevention. The easiest, fastest and most flexible solution is an inflatable decontamination shower.

- **FASTEST, MOST FLEXIBLE DECON SOLUTION**
- **UNINTENDED CONTAMINATION PREVENTED**
- **ESPECIALLY DESIGNED FOR EASY HANDLING AND QUICK SETUP**
- **RELIABLE DECONTAMINATION SYSTEM PROVEN IN PRACTICAL SITUATIONS**

// DECONTAMINATION SHOWERS

FRAME

Inflatable frame, operated with 0.3 bar overpressure, made of airtight coated fabric 850 g/m², connected to the shower cabin with a 'cord and loop system'. The frame is inflated with compressed air or by using an electric blower within approx. 1 minute; the relief valve prevents the frame from overfilling.

SHOWER CABIN FABRIC AND GROUND SHEET

The shower cabin is made of yellow PVC treated polyester fabric, waterproof, anti fungicidal and has large transparent foil windows. The groundsheet is permanently attached to the shower and made of grey PVC-coated polyester fabric.

SHOWER EQUIPMENT

Arched tubular system containing nozzles, hand shower with a 1.5 m hose, D-coupling head for water supply, C-coupling head for water discharge.

ADVANTAGES

- Short erecting time and small manpower demand
- Small damages can be repaired on site
- Easy cleaning
- Separation of shower cabin and frame
- System proven in practical situations

SAFETY

- Partition walls and thresholds prevent a carryover of unintended contamination
- Relief valve prevents from overfilling the tubular system
- Inflatable frame made of PVC
- Flame retardant fabric, according to DIN 4102 B1, available



ARZ 2x2



ARZ 2x2 with tub



ARZ 2x3

ARZ 2x3 with tub

ARZ 3x4.4

	ARZ 2x2	ARZ 2x2 with tub	ARZ 2x3	ARZ 2x3 with tub	ARZ 3x4.4
Length	2.00 m	3.80 m	3.00 m	4.80 m	4.50 m
Width	2.00 m	2.00 m	2.00 m	2.00 m	3.00 m
Height	2.50 m	2.50 m	2.50 m	2.50 m	2.60 m
Weight	44 kg	61 kg	75 kg	90 kg	135 kg
Nozzles	5	5	10	10	10
Hand showers	1	1	2	2	2
Hose arches	1	1	2	2	2
Tub	-	1.80 x 2.00 m	-	1.80 x 2.00 m	-

STANDARD EQUIPMENT

Shower system with 5/10 nozzles and 1/2
Hand showers (depending on shower size)
Storz D-coupling for water supply
Storz C-coupling for water discharge
Floor grid
Carrying bag
Pegs
Guy ropes
Hand pump
Repair kit
Manual and maintenance instructions

LANCO
Dr. Lange GmbH & Co. KG
Sure Wisch 6
30625 Hannover

LANCO

Telephone: +49 (0)511 367155-0
Fax: +49 (0)511 367155-140
Email: info@lanco-tents.com
Internet: www.lanco-tents.com